

## DEF Do's and Don'ts AUS 32, High Quality Urea Solution



- ✓ When filling, maintain the highest level of cleanliness so that dust and contaminants are prevented from entering the storage tank.
- ✓ Clean the pump nozzle after filling, dip it in a tub of clean tap water in order to eliminate possible white crusty deposits of dried out **AUS 32**.
- ✓ When filling vehicle tanks with **AUS 32** at service stations, there is no requirement to wear protective clothing.
- ✓ Do wear safety goggles and protective gloves when handling **AUS 32**.

In case of contact with the eyes, rinse immediately with plenty of water.

In case of contact with the skin, wash immediately with soap and plenty of water. If pain is experienced or you feel unwell, consult a doctor.

- ✓ In the case of fire, **AUS 32** containers must be cooled by spraying with water. This will reduce the danger of rapid decomposition of **AUS 32** (at temperatures over 80° C) and the resultant danger of containers bursting. After a fire, the contents of any **AUS 32** containers must be disposed of.

- ☒ Do not store **AUS 32** close to foodstuffs or animal feed.
- ☒ Do not keep **AUS 32** in the sunlight or a warm place.
- ☒ Do not keep any clothing on which **AUS 32** has been spilt. Stains can be easily washed out with water.
- ☒ Do not swallow – if so immediately drink plenty of water.
- ☒ Do not spill **AUS 32** – if so immediately clean affected objects, surfaces or area of ground with water. Caution: danger of slipping. **AUS 32** can be harmful to concrete and masonry.
- ☒ Do not pour **AUS 32** into the drainage system – Spilt **AUS 32** should be properly disposed of as waste.
- ☒ Do not use **AUS 32** if it has been mixed with water or diesel fuel.